

| Dual Zone                           | Cooling                          |                                  | Heat Pumps                       |                                  |
|-------------------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|
| FEATURES                            | MMC18DA-1                        | MMC24DA-1                        | MMH18DA-1                        | MMH24DA-1                        |
| System Cooling Capacity (230V/208V) | 18,000/18,000                    | 23,600/24,000                    | 18,000/18,000                    | 23,600/24,000                    |
| Cooling Cap./Zone (230V/208V)       | 9,000/9,000                      | 11,800/12,000                    | 9,000/9,000                      | 11,800/12,000                    |
| System Heating Capacity (230V/208V) | N/A                              | N/A                              | 18,000                           | 24,000                           |
| Heating Cap./Zone (230V/208V)       | N/A                              | N/A                              | 9,000                            | 12,000                           |
| SEER                                | 13                               | 13                               | 13                               | 13                               |
| Dehumidify (Pint/hr) per zone       | 2.3                              | 2.5                              | 2.3                              | 2.5                              |
| HSPF                                | N/A                              | N/A                              | 7.7                              | 7.7                              |
| Air Flow (CFM H/M/L)                | 289/271/254                      | 332/314/296                      | 289/271/254                      | 332/314/296                      |
| Fan Speed (C/H/F)                   | 4/-/3                            | 4/-/3                            | 4/3/3                            | 4/3/3                            |
| <b>Indoor Unit Dimensions</b>       |                                  |                                  |                                  |                                  |
| Width (inches)                      | 33                               | 35 <sup>3</sup> / <sub>16</sub>  | 33                               | 35 <sup>3</sup> / <sub>16</sub>  |
| Height (inches)                     | 10 <sup>5</sup> / <sub>8</sub>   | 11 <sup>1</sup> / <sub>8</sub>   | 10 <sup>5</sup> / <sub>8</sub>   | 11 <sup>1</sup> / <sub>8</sub>   |
| Depth (inches)                      | 6                                | 6 <sup>1</sup> / <sub>2</sub>    | 6                                | 6 <sup>1</sup> / <sub>2</sub>    |
| Net wt./Shipping wt. (lbs)          | 15.4/18.1                        | 20.5/24                          | 15.4/18.1                        | 20.5/24                          |
| <b>Outdoor Unit Dimensions</b>      |                                  |                                  |                                  |                                  |
| Width (inches)                      | 34 <sup>5</sup> / <sub>16</sub>  | 34 <sup>5</sup> / <sub>16</sub>  | 34 <sup>5</sup> / <sub>16</sub>  | 34 <sup>5</sup> / <sub>16</sub>  |
| Height (inches)                     | 25 <sup>13</sup> / <sub>16</sub> | 31 <sup>13</sup> / <sub>16</sub> | 25 <sup>13</sup> / <sub>16</sub> | 31 <sup>13</sup> / <sub>16</sub> |
| Depth (inches)                      | 12 <sup>5</sup> / <sub>8</sub>   | 12 <sup>5</sup> / <sub>8</sub>   | 12 <sup>5</sup> / <sub>8</sub>   | 12 <sup>5</sup> / <sub>8</sub>   |
| Net wt./Shipping wt. (lbs)          | 125.7/134.7                      | 141.1/151.9                      | 125.7/134.7                      | 141.1/151.9                      |

**Power Supply**  
208-230V/1/60

| Tri Zone                            | Cooling                          | Heat Pump                        |
|-------------------------------------|----------------------------------|----------------------------------|
| FEATURES                            | MMC36TA-1                        | MMH36TA-1                        |
| System Cooling Capacity (230V/208V) | 35,200/36,000                    | 35,200/36,000                    |
| Cooling Cap./Zone (230V/208V)       | 11,730/12,000                    | 11,730/12,000                    |
| System Heating Capacity (230V/208V) | N/A                              | 36,000                           |
| Heating Cap./Zone (230V/208V)       | N/A                              | 12,000                           |
| SEER                                | 13                               | 13                               |
| Dehumidify (Pint/hr) per zone       | 2.5                              | 2.5                              |
| HSPF                                | N/A                              | 7.7                              |
| Air Flow (CFM H/M/L)                | 332 / 314 / 296                  | 332 / 314 / 296                  |
| Fan Speed (C/H/F)                   | 4 / - / 3                        | 4 / 3 / 3                        |
| <b>Indoor Unit Dimensions</b>       |                                  |                                  |
| Width (inches)                      | 35 <sup>3</sup> / <sub>16</sub>  | 35 <sup>3</sup> / <sub>16</sub>  |
| Height (inches)                     | 11 <sup>1</sup> / <sub>8</sub>   | 11 <sup>1</sup> / <sub>8</sub>   |
| Depth (inches)                      | 6 <sup>1</sup> / <sub>2</sub>    | 6 <sup>1</sup> / <sub>2</sub>    |
| Net wt./Shipping wt. (lbs)          | 20.5/24                          | 20.5/24                          |
| <b>Outdoor Unit Dimensions</b>      |                                  |                                  |
| Width (inches)                      | 34 <sup>5</sup> / <sub>16</sub>  | 34 <sup>5</sup> / <sub>16</sub>  |
| Height (inches)                     | 40 <sup>11</sup> / <sub>16</sub> | 40 <sup>11</sup> / <sub>16</sub> |
| Depth (inches)                      | 12 <sup>5</sup> / <sub>8</sub>   | 12 <sup>5</sup> / <sub>8</sub>   |
| Net wt./Shipping wt. (lbs)          | 185.2/201.5                      | 185.2/201.5                      |



Multi-zone systems allow you to condition two or three rooms with one outdoor unit tied to two or three indoor units (depending on model chosen). Multi-zone models include all the great features of the Comfort-Aire ductless mini-split line including triple filtration, auto operation, multiple modes and easy installation.

**DUAL ZONE**

18,000 - 24,000 BTUH  
9,000 - 12,000 per zone



Dual Zone unit comes with two wireless remotes, one for each air handler.



**TRI ZONE**

36,000 BTUH  
12,000 per zone

Unit comes with three wireless remotes, one for each air handler.



CERTIFICATION APPLIES ONLY WHEN COMPLETE SYSTEM IS LISTED WITH AHRI

