

SPECIFICATIONS RSG13 Series Models

Model	Nom. Cap.BTUH	SEER*	Power (60 Hz)	Connection (In. ODS)		Line Size (in.)	Dimensions HxDxW (inches)	Shipping Weight
				Liquid	Suction			
RSG1318-1A	18,000	13	208-230/1	3/8	3/4	3/8-3/4	24 ¹ / ₄ x 23 ⁵ / ₈ x 23 ⁵ / ₈	135
RSG1324-1A	24,000	13	208-230/1	3/8	3/4	3/8-3/4	24 ¹ / ₄ x 23 ⁵ / ₈ x 23 ⁵ / ₈	134
RSG1330-1A	29,600	13	208-230/1	3/8	3/4	3/8-3/4	24 ¹ / ₄ x 27 ⁵ / ₈ x 27 ⁵ / ₈	154
RSG1336-1A	34,600	13	208-230/1	3/8	7/8	3/8-7/8	27 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	178
RSG1342-1A	41,500	13	208-230/1	3/8	7/8	3/8-7/8	27 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	206
RSG1348-1A	47,000	13	208-230/1	3/8	7/8	3/8-1-1/8	27 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	233
RSG1360-1A	56,500	13	208-230/1	3/8	7/8	3/8 -1-1/8	35 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	238

Units come pre-charged with R-410A for a 15' line set.

Capacities will vary slightly depending on air handler and/or coil used with system.

Design, specifications and material subject to change without notice.

* SEER ratings with AHGV and HAGV variable speed air handlers are 14, except RSG1360 at 13.5 SEER.



UNITS ARE CERTIFIED AND RATED UNDER AHRI STANDARD 210/240 FOR UNITARY AIR CONDITIONERS WHEN INSTALLED AS A MATCHED SYSTEM