

Models	Input BTUH	Heating Cap. BTUH	AFUE*	Motor HP	Motor Full Load Amps	Blower (DxW)	Dimensions H x W x D (inches)	Shipping Wt. (lbs)
UPFLOW								
GLUA45-E3B	45,000	42,000	93.5%	½	6.8	11 x 7	34 x 17½ x 28 ¹³ / ₁₆	111
GLUA60-E3B	60,000	56,000	92.5%	½	6.8	11 x 7	34 x 17½ x 28 ¹³ / ₁₆	117
GLUA75-E3C	75,000	70,000	92.8%	½	6.8	11 x 7	34 x 17½ x 28 ¹³ / ₁₆	123
GLUA75-E4C	75,000	70,000	92.0%	¾	9.5	12 x 7	34 x 21 x 28 ¹³ / ₁₆	123
GLUA90-E4B	90,000	84,000	93.5%	½	8.0	12 x 11	34 x 21 x 28 ¹³ / ₁₆	148
GLUA105-E5B	105,000	97,000	92.0%	¾	9.5	12 x 11	34 x 21 x 28 ¹³ / ₁₆	152
GLUA120-E5B	120,000	113,000	93.5%	¾	9.5	11 x 10	34 x 24½ x 28 ¹³ / ₁₆	160
DOWNFLOW/HORIZONTAL								
GLDH45-E3B	45,000	42,000	92.0%	½	6.8	11 x 7	34 x 17½ x 28 ¹³ / ₁₆	111
GLDH60-E3B	60,000	56,000	92.4%	½	6.8	11 x 7	34 x 17½ x 28 ¹³ / ₁₆	117
GLDH75-E3B	75,000	70,000	92.0%	½	6.8	11 x 7	34 x 17½ x 28 ¹³ / ₁₆	123
GLDH75-E4B	75,000	70,000	92.3%	¾	9.5	12 x 7	34 x 21 x 28 ¹³ / ₁₆	123
GLDH90-E4B	90,000	84,000	92.4%	½	8.0	12 x 11	34 x 21 x 28 ¹³ / ₁₆	148
GLDH105-E5B	105,000	97,000	92.0%	¾	9.5	12 x 11	34 x 21 x 28 ¹³ / ₁₆	152
GLDH120-E5B	120,000	113,000	92.1%	¾	9.5	11 x 10	34 x 24½ x 28 ¹³ / ₁₆	160

*AFUE—Annual Fuel Utilization Efficiency

NOTE: Horizontal installation is for right side only with air supply on the left

**Limited lifetime warranty on heat exchangers;
limited 12 year warranty on other parts**
(Some limitations apply; see printed warranty for details.)