

Models	Input BTUH	Heating Cap. BTUH	AFUE*	Nom. Tons Cooling	Motor HP	Motor Full Load Amps	Blower (DxW)	Dimensions H x W x D (inches)	Shipping Wt. (lbs.)
UPFLOW/HORIZONTAL									
GMUH50-E3A	50,000	41,000	81.4%	3	1/2	6.8	11x6	34 x 14 x 28 ^{13/16}	85
GMUH75-E3A	75,000	60,000	80.6%	3	1/2	5.8	11x6	34 x 17 ^{1/2} x 28 ^{13/16}	105
GMUH75-E4A	75,000	60,000	80.5%	4	1/2	7.9	11x7	34 x 17 ^{1/2} x 28 ^{13/16}	105
GMUH100-E3A	100,000	80,000	80.0%	3	1/2	7.1	11x7	34 x 17 ^{1/2} x 28 ^{13/16}	115
GMUH100-E5A	100,000	80,000	80.0%	5	3/4	9.5	11x10	34 x 21 x 28 ^{13/16}	120
GMUH125-E5A	125,000	99,000	80.0%	5	3/4	9.5	11x10	34 x 24 ^{1/2} x 28 ^{13/16}	140
GMUH150-E5A	150,000	119,000	80.0%	5	3/4	9.5	11x10	34 x 24 ^{1/2} x 28 ^{13/16}	150
DOWNFLOW									
GMDA50-E3A	50,000	41,000	82.2%	3	1/2	6.8	11x6	34 x 14 x 28 ^{13/16}	85
GMDA75-E3A	75,000	60,000	80.5%	3	1/2	5.8	11x6	34 x 17 ^{1/2} x 28 ^{13/16}	105
GMDA75-E4A	75,000	60,000	81.1%	4	1/2	7.9	11x7	34 x 17 ^{1/2} x 28 ^{13/16}	105
GMDA100-E3A	100,000	80,000	80.2%	3	1/2	7.1	11x7	34 x 17 ^{1/2} x 28 ^{13/16}	115
GMDA100-E5A	100,000	80,000	80.0%	5	3/4	9.5	11x10	34 x 21 x 28 ^{13/16}	120
GMDA125-E5A	125,000	99,000	80.0%	5	3/4	9.5	11x10	34 x 24 ^{1/2} x 28 ^{13/16}	140
GMDA150-E5A	150,000	120,000	80.0%	5	3/4	9.5	11x10	34 x 24 ^{1/2} x 28 ^{13/16}	150

* AFUE - Annual Fuel Utilization Efficiency