

### 80% AFUE GAS FURNACES

#### GFM80S FEATURES

- Durable aluminized steel tubular heat exchanger
- Hot-surface ignition for dependable operation
- Quiet multi-speed ECM blower motor
- Designed for multi-position installation: Upflow, downflow, horizontal
- Natural gas and propane (LP) convertible, LP kit Included
- Industry-standard cabinet sizes for easy replacement, installation and add-on cooling
- Convenient left or right connection for gas and electric service
- Removable base for side or bottom return application



#### GFM80S SPECS AT A GLANCE

Model	AFUE	BTU Input	Configuration	Dimensions (in.) (H x W x D)
GFM80S040A3S1A	80%	40,000	Upflow/Downflow/Horizontal	34-1/2 x 14-1/2 x 28-1/2
GFM80S060A3S1A	80%	60,000	Upflow/Downflow/Horizontal	34-1/2 x 14-1/2 x 28-1/2
GFM80S060B4S1A	80%	60,000	Upflow/Downflow/Horizontal	34-1/2 x 17-1/2 x 28-1/2
GFM80S080B4S1A	80%	80,000	Upflow/Downflow/Horizontal	34-1/2 x 17-1/2 x 28-1/2
GFM80S080C4S1A	80%	80,000	Upflow/Downflow/Horizontal	34-1/2 x 21 x 28-1/2
GFM80S100C5S1A	80%	100,000	Upflow/Downflow/Horizontal	34-1/2 x 21 x 28-1/2
GFM80S120D5S1A	80%	120,000	Upflow/Downflow/Horizontal	34-1/2 x 24-1/2 x 28-1/2



### 96% AFUE GAS FURNACES

#### GFM96T FEATURES

- Durable aluminized steel tubular heat exchanger.
- Stainless-steel secondary heat exchanger
- Two-stage gas valve
- Hot surface ignition for dependable operation
- Quiet multi-speed ECM blower motor
- Control board with self-diagnostics and low-voltage terminal block
- Natural gas and propane (LP) convertible
- Designed for multi-position installation: Upflow and horizontal
- Industry-standard cabinet sizes for easy replacement, installation and add-on cooling
- Convenient left or right connection for gas and electric service
- Removable base for side or bottom return applications



#### GFM96T SPECS AT A GLANCE

Model	AFUE	BTU Input	Configuration	Dimensions (in.) (H x W x D)
GFM96T060B3S1A	96%	60,000	Upflow/Horizontal	34-1/2 x 17-1/2 x 28-1/2
GFM96T080B3S1A	96%	80,000	Upflow/Horizontal	34-1/2 x 17-1/2 x 28-1/2
GFM96T080C4S1A	96%	80,000	Upflow/Horizontal	34-1/2 x 21 x 28-1/2
GFM96T100C5S1A	96%	100,000	Upflow/Horizontal	34-1/2 x 21 x 28-1/2
GFM96T100D5S1A	96%	100,000	Upflow/Horizontal	34-1/2 x 24-1/2 x 28-1/2
GFM96T120D5S1A	96%	120,000	Upflow/Horizontal	34-1/2 x 24-1/2 x 28-1/2

